

CT 8052 HS

CUTTING OIL - NON-CHLORINATED

▶ PRODUCT DESCRIPTION

CT 8052 HS is a high performance, non-chlorinated cutting oil. CT 8052-HS has a noncorrosive high performance EP and lubricity package to provide machining capability on a multitude of metals. The use of the CT 8052-HS as both the cutting oil and lube oil assures excellent machinability and eliminates additive dilution on the cutting side.

▶ FEATURED BENEFITS

- Provides one product for the operation of the machine shop
- High performance EP package provides excellent performance on a variety of metals
- A chlorine free cutting oil
- Will not stain non-ferrous materials
- Can be used for machining as well as grinding
- Contains an anti-mist additive for cleaner work environment
- Low odor and transparent appearance provide good operator acceptance

▶ APPROVALS

- Super-compliant for California SCAQMD Rule 1144

APPLICATION



COMPATIBLE METALS

Carbon Steel
Tool Steel
Stainless Steel
Aluminum Alloys
Copper Alloys

MACHINING CAPABILITIES

Free machining
Turning
Threading
Tapping
Broaching
Grinding

FOAMING CHARACTERISTICS

Moderate

FILM TYPE

Oily

RUST PROTECTION

None





TYPICAL PROPERTIES

Fluid Type	Straight oil, mild to moderate alkaline cleaner
Appearance	Light amber liquid
Odor	Mild petroleum
Weight, 60°F (15.6°C)	7.2 lbs/gal.
Viscosity, 40°C	14.5 cSt
Flash Point, COC	330°F (165°C)
Sulfur	Present
Ester	Present for polar lubricity
Phosphorus	Present for anti-wear
Falex EP Extreme Pressure Lubricity Test	Pass 4,500 lbs.
VOC, ASTM E 1868	5.1 grams/liter

PRODUCT APPLICATION / USAGE

CT 8052 HS can be used to machine ferrous metals with machinability ratings below 50% up through free machining steels. The product is also safe on aluminum and copper alloys. CT 8052- HS can be used for turning, drilling, gun drilling, tapping, broaching, grinding and most any other machining operation.

PRODUCT CODE

2547200000

HEALTH AND SAFETY

For health and safety guidance, please refer to the Chemtool SDS (Safety Data Sheets).